



产品描述: 间距: 5.08mm 额定电压: 320V

额定电流：12A 接线方式：螺钉接线 颜色：可定制

The technical drawings show the following dimensions:

- Front View (Top Left):** Shows a row of terminals with a pitch dimension of 1.00.
- Side View (Bottom Left):** Shows the profile of the terminal block with dimensions 8.45, 7.80, 9.30, 19.20, and 15.00. The text "P-1000" is visible on the side.
- Top View (Right):** Shows the top of the terminal block with a width dimension of 7.70.
- Front View (Bottom Right):** Shows another perspective of the terminals with dimensions 5.08, 7.60, and formulas for overall dimensions: $\text{Dim. a} = 5.08 \times (P - 1)$ and $\text{Dim. b} = 5.08 \times P + 10.12$.

参数

产品型号	MC-PB5.08H14C-I-0001
产品间距	5.08
产品层数	单层
接线位数	14

☞ 接线方式	螺钉接线
☞ 防护等级	IP20
☞ 工作温度	-40~+105℃
☞ 绝缘材料	PA66
☞ 绝缘材料组别	I
☞ 导电体材料	Copper alloy
☞ 导电体表面镀层	Sn,Plated
☞ 颜色	绿/黑/蓝/灰/橙/红

技术数据

☞ 额定电流（IEC）	12A
☞ 额定电压（IEC）	320V
☞ 过压类别	III III II
☞ 污染等级	3 2 2
☞ 额定冲击电压	4.0KV 4.0KV 4.0KV
☞ 硬导线截面积	0.2-2.5mm ²
☞ 柔性导线截面积	0.2-2.5mm ²
☞ 柔性导线截面积，带绝缘管套	0.2-2.5mm ²
☞ 锁线螺钉规格	M3
☞ 锁线螺钉扭矩	0.5N.m
☞ 固定螺钉规格	-
☞ 固定螺钉扭矩	-
☞ 剥线长度	7-8mm
☞ 使用组别	B/C/D

商业数据

订货号

MC-PB5.08H14C-I-0001

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

邮编：315303

Switchboard: +86 574-63288158

总机：+86 574-63288158

Fax: +86 574-63288170

传真：+86 574-63288170

E-mail：supucontact@supu.cn

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

服务热线：400-626-6336



官方微信