



产品描述: 间距：3.5mm 额定电压：160V
额定电流：8A 颜色：可定制

Technical drawing of a rectangular plate with dimensions and hole patterns. The drawing shows a rectangular plate with overall dimensions of 5.50 (width) by 2.55 (height). The plate features a central rectangular area with a width of 3.50 and a height of 5.50. This central area contains a grid of holes. The holes are arranged in two rows, with a vertical spacing of 3.50 between the rows. The horizontal spacing between the holes is 3.50. The holes have a diameter of $\phi 1.40$. The distance from the left edge of the plate to the first hole is 5.50. The distance from the right edge of the plate to the last hole is 1.60. The distance from the top edge of the plate to the first hole is 5.50. The distance from the bottom edge of the plate to the last hole is 5.50. The distance from the center of the first hole to the center of the last hole is $3.50 \times (P/2 - 1)$. The distance from the center of the first hole to the center of the last hole is also 3.50. The distance from the center of the first hole to the center of the last hole is also 5.50. The distance from the center of the first hole to the center of the last hole is also 1.60. The distance from the center of the first hole to the center of the last hole is also $\phi 1.80$.

参数

☞ 产品型号	MC-DPT3.5V14-F-BK-2000
☞ 产品间距	3.5
☞ 接线位数	14
☞ 接线方式	-

⌘ 防护等级	IP20
⌘ 工作温度	-40~+105°C
⌘ 绝缘材料	PA66
⌘ 绝缘材料组别	I
⌘ 导电体材料	Copper alloy
⌘ 导电体表面镀层	Sn,Plated
⌘ 颜色	绿/黑/蓝/灰/橙/红

技术数据

⌘ 额定电流（IEC）	8A
⌘ 额定电压（IEC）	160V
⌘ 过压类别	III III II
⌘ 污染等级	3 2 2
⌘ 额定冲击电压	- 2.5KV 2.5KV
⌘ 额定电流（UL）	8A - -
⌘ 额定电压(UL)	150V - -
⌘ 硬导线截面积	-
⌘ 柔性导线截面积	-
⌘ 柔性导线截面积，带绝缘管套	-
⌘ 锁线螺钉规格	-
⌘ 锁线螺钉扭矩	-
⌘ 固定螺钉规格	-
⌘ 剥线长度	-
⌘ 使用组别	B/C/D

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

邮编：315303

Switchboard: +86 574-63288158

总机：+86 574-63288158

Fax: +86 574-63288170

传真：+86 574-63288170

E-mail：supucontact@supu.cn

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

服务热线：400-626-6336



官方微信