


产品名称:MC-PA2.5H13-0002

额定电流：4A 颜色：可定制



Technical drawing of the P.C.B. LAYOUT showing top and side views with dimensions.

Top View Dimensions:

- Overall width: 8.10
- Distance from left edge to first component: 2.20
- Distance between components: 2.50
- Dimension a (distance between components): Dim.a
- Overall width dimension: Dim.b = $a + 4.4$

Side View Dimensions:

- Distance from left edge to first component: 2.20
- Distance between components: 2.50
- Dimension a (distance between components): Dim.a
- Reference dimension: Ref. ($\phi 1.20$)
- Overall height dimension: 1.20

P.C.B. LAYOUT

参数

☞ 产品型号	MC-PA2.5H13-0002
☞ 产品间距	2.5
☞ 接线位数	13
☞ 接线方式	-

⌘ 防护等级	IP20
⌘ 工作温度	-40~+105°C
⌘ 绝缘材料	PA66
⌘ 绝缘材料组别	I
⌘ 导电体材料	Copper alloy
⌘ 导电体表面镀层	Sn,Plated
⌘ 颜色	绿/黑/蓝/灰/橙/红

技术数据

⌘ 额定电流（IEC）	4A
⌘ 额定电压（IEC）	160V
⌘ 过压类别	III III II
⌘ 污染等级	3 2 2
⌘ 额定冲击电压	1.5KV 2.5KV 2.5KV
⌘ 额定电流（UL）	4A - -
⌘ 额定电压(UL)	125V - -
⌘ 硬导线截面积	-
⌘ 柔性导线截面积	-
⌘ 柔性导线截面积，带绝缘管套	-
⌘ 锁线螺钉规格	-
⌘ 锁线螺钉扭矩	-
⌘ 固定螺钉规格	-
⌘ 剥线长度	-
⌘ 使用组别	B/C/D

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

邮编：315303

Switchboard: +86 574-63288158

总机：+86 574-63288158

Fax: +86 574-63288170

传真：+86 574-63288170

E-mail：supucontact@supu.cn

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

服务热线：400-626-6336



官方微信