




产品名称:MC-PA3.81V02-0002



额定电流：8A 颜色：可定制

Technical drawing of a stepped profile. The profile consists of a base section and a raised section. The base section has a width of 3.50 ± 0.30 and a height of 3.00 . The raised section has a width of 9.20 and a height of 7.25 . A small rectangular feature is located on the top surface of the base section, with a width of 0.80 . The drawing is a side view, showing the profile of the object.



参数

产品型号	MC-PA3.81V02-0002
产品间距	3.81
接线位数	2
接线方式	-

⌘ 防护等级	IP20
⌘ 工作温度	-40~+105°C
⌘ 绝缘材料	PA66
⌘ 绝缘材料组别	I
⌘ 导电体材料	Copper alloy
⌘ 导电体表面镀层	Sn,Plated
⌘ 颜色	绿/黑/蓝/灰/橙/红

技术数据

⌘ 额定电流（IEC）	8A
⌘ 额定电压（IEC）	160V
⌘ 过压类别	III III II
⌘ 污染等级	3 2 2
⌘ 额定冲击电压	2.5KV 2.5KV 2.5KV
⌘ 额定电流（UL）	8A - 8A
⌘ 额定电压(UL)	300V - 300V
⌘ 硬导线截面积	-
⌘ 柔性导线截面积	-
⌘ 柔性导线截面积，带绝缘管套	-
⌘ 锁线螺钉规格	-
⌘ 锁线螺钉扭矩	-
⌘ 固定螺钉规格	-
⌘ 剥线长度	-
⌘ 使用组别	B/C/D

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

邮编：315303

Switchboard: +86 574-63288158

总机：+86 574-63288158

Fax: +86 574-63288170

传真：+86 574-63288170

E-mail：supucontact@supu.cn

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

服务热线：400-626-6336



官方微信