


产品名称:MC-PA5.08V13-D-0002



Technical drawing of the PCB layout for the 100-pin connector. The drawing includes three views: a side profile, a top view, and a bottom view.

Side Profile View:

- Total length: 12.00
- Mounting hole diameter: 3.80
- Mounting hole offset: 1.00
- Mounting hole diameter: 3.80
- Mounting hole offset: 1.00

Top View:

- Total width: 19.91
- Pitch: 5.08
- Total width formula: $5.08 \times (P-1) + 7.08$

Bottom View:

- Total width: 3.80
- Pitch: 5.08
- Total width formula: $5.08 \times (P-1)$
- Mounting hole diameter: 3.80
- Mounting hole offset: 1.00

PCB LAYOUT

产品型号	MC-PA5.08V13-D-0002
产品间距	5.08
接线位数	13
接线方式	-

⌘ 防护等级	IP20
⌘ 工作温度	-40~+105°C
⌘ 绝缘材料	PA66
⌘ 绝缘材料组别	I
⌘ 导电体材料	Copper alloy
⌘ 导电体表面镀层	Sn,Plated
⌘ 颜色	绿/黑/蓝/灰/橙/红

技术数据

⌘ 额定电流（IEC）	18A
⌘ 额定电压（IEC）	320V
⌘ 过压类别	III III II
⌘ 污染等级	3 2 2
⌘ 额定冲击电压	4.0KV 4.0KV 4.0KV
⌘ 额定电流（UL）	15A - 10A
⌘ 额定电压(UL)	300V - 300V
⌘ 硬导线截面积	-
⌘ 柔性导线截面积	-
⌘ 柔性导线截面积，带绝缘管套	-
⌘ 锁线螺钉规格	-
⌘ 锁线螺钉扭矩	-
⌘ 固定螺钉规格	-
⌘ 剥线长度	-
⌘ 使用组别	B/C/D

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

邮编：315303

Switchboard: +86 574-63288158

总机：+86 574-63288158

Fax: +86 574-63288170

传真：+86 574-63288170

E-mail：supucontact@supu.cn

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

服务热线：400-626-6336



官方微信