


产品名称:MC-PA7.62H03-G-0002



额定电流：18A 颜色：可定制

Figure 1: Dimensions of the PCB layout. The figure consists of three views: a side view (top left), a top view (top right), and a bottom view (bottom center). The side view shows a component with a total width of 12.00, a central pin width of 2.00, and a total height of 8.45. The top view shows a row of pins with a center-to-center pitch of 7.62, a pin diameter of 1.40, and a total width of $7.62X(P-1) + 5.62$. The bottom view shows the same pin layout from below, with a total width of $7.62X(P-1)$ and a total height of 2.00. The text "PCB LAYOUT" is centered at the bottom.

参数

☞ 产品型号	MC-PA7.62H03-G-0002
☞ 产品间距	7.62
☞ 接线位数	3
☞ 接线方式	-

⌘ 防护等级	IP20
⌘ 工作温度	-40~+105°C
⌘ 绝缘材料	PA66
⌘ 绝缘材料组别	I
⌘ 导电体材料	Copper alloy
⌘ 导电体表面镀层	Sn,Plated
⌘ 颜色	绿/黑/蓝/灰/橙/红

技术数据

⌘ 额定电流（IEC）	18A
⌘ 额定电压（IEC）	630V
⌘ 过压类别	III III II
⌘ 污染等级	3 2 2
⌘ 额定冲击电压	6.0KV 6.0KV 6.0KV
⌘ 额定电流（UL）	15A - 10A
⌘ 额定电压(UL)	300V - 300V
⌘ 硬导线截面积	-
⌘ 柔性导线截面积	-
⌘ 柔性导线截面积，带绝缘管套	-
⌘ 锁线螺钉规格	-
⌘ 锁线螺钉扭矩	-
⌘ 固定螺钉规格	-
⌘ 剥线长度	-
⌘ 使用组别	B/C/D

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

邮编：315303

Switchboard: +86 574-63288158

总机：+86 574-63288158

Fax: +86 574-63288170

传真：+86 574-63288170

E-mail：supucontact@supu.cn

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

服务热线：400-626-6336



官方微信