


产品名称:MC-PD5.08V05-F-0001

额定电流：8A 颜色：可定制



Technical drawing of the PCB layout for the 120W power module. The drawing includes a side view and a top view.

Side View Dimensions:

- Height: 3.00
- Width: 9.20
- Depth: 7.25
- Overall width: 3.50 ± 0.30

Top View Dimensions:

- Overall width: 4.50
- Overall length: $5.08 \times P + 9.12$
- Distance between mounting holes: $5.08 \times (P - 1)$
- Distance from edge to first mounting hole: 7.10
- Distance from edge to first through-hole pad: 4.50
- Distance between through-hole pads: 5.08
- Distance from edge to last through-hole pad: 7.10
- Distance between last through-hole pad and last mounting hole: 4.50
- Distance between last mounting hole and last edge: 7.10

PCB LAYOUT:

- Overall width: 3.00
- Overall length: 7.25
- Mounting holes: 12 holes with diameter $\phi 1.20$
- Through-hole pads: 6 pads with diameter $\phi 2.40$

参数

☞ 产品型号	MC-PD5.08V05-F-0001
☞ 产品间距	5.08
☞ 接线位数	5
☞ 接线方式	-

⌘ 防护等级	IP20
⌘ 工作温度	-40~+105°C
⌘ 绝缘材料	PA66
⌘ 绝缘材料组别	I
⌘ 导电体材料	Copper alloy
⌘ 导电体表面镀层	Sn,Plated
⌘ 颜色	绿/黑/蓝/灰/橙/红

技术数据

⌘ 额定电流（IEC）	8A
⌘ 额定电压（IEC）	320V
⌘ 过压类别	III III II
⌘ 污染等级	3 2 2
⌘ 额定冲击电压	4.0KV 4.0KV 4.0KV
⌘ 额定电流（UL）	8A - 8A
⌘ 额定电压(UL)	300V - 300V
⌘ 硬导线截面积	-
⌘ 柔性导线截面积	-
⌘ 柔性导线截面积，带绝缘管套	-
⌘ 锁线螺钉规格	-
⌘ 锁线螺钉扭矩	-
⌘ 固定螺钉规格	-
⌘ 剥线长度	-
⌘ 使用组别	B/C/D

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

邮编：315303

Switchboard: +86 574-63288158

总机：+86 574-63288158

Fax: +86 574-63288170

传真：+86 574-63288170

E-mail：supucontact@supu.cn

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

服务热线：400-626-6336



官方微信