



产品描述: 间距：3.5mm 额定电压：150V
额定电流：8A 连接方式：直插弹簧接线
颜色：可定制

Technical drawing of the 12-pin connector showing top and side views with dimensions.

Top View Dimensions:

- Overall width: $3.5 \times (P/2 - 1) + 4.3$
- Pin pitch (center-to-center): $3.5 \times (P/2 - 1)$
- Pin diameter: 3.10
- Pin height: 3.50
- Overall height: 13.25

Side View Dimensions:

- Overall height: 22.45
- Height from base to top of housing: 15.40
- Base pin diameter: M2*0.4

参数

☞ 产品型号	MC-DRT3.5H22P-K-0001
☞ 产品间距	3.5
☞ 接线位数	22
☞ 接线方式	直插弹簧接线

☞ 防护等级	IP20
☞ 工作温度	-40~+105℃
☞ 绝缘材料	PA66
☞ 绝缘材料组别	I
☞ 导电体材料	Copper alloy
☞ 导电体表面镀层	Sn,Plated
☞ 颜色	绿/黑/蓝/灰/橙/红

商业数据

☞ 订货号	MC-DRT3.5H22P-K-0001
-------	----------------------

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303	邮编：315303
Switchboard: +86 574-63288158	总机：+86 574-63288158
Fax: +86 574-63288170	传真：+86 574-63288170
E-mail：supucontact@supu.cn	E-mail：supucontact@supu.cn
Service Hotline: 400-626-6336	服务热线：400-626-6336



官方微信

文件日期：2025-06-17 02:50

数据修改权利归速普所有。