

产品名称:MC-TC-B10.0H09P-0001

颜色：可定制



PCB LAYOUT

The PCB layout shows a square board with dimensions 29.00 x 30.00. The top view includes a central circular feature labeled "SUPPLY NC-TC10.01". The bottom view shows a 10.00x(P-1) array of components, with dimensions 4.45, 2.50, 5.00, 1.00, 15.00, 11.50, 1.20, and 10.00. The layout also shows a 10.00x(P-1) array of components on the right side, with dimensions 10.00xP+1.80 and 1.20.

参数

产品型号	MC-TC-B10.0H09P-0001
产品间距	10
产品层数	单层
接线位数	9

☞ 接线方式	直插弹簧接线
☞ 防护等级	IP20
☞ 工作温度	-40~+105℃
☞ 绝缘材料	PA66
☞ 绝缘材料组别	I
☞ 导电体材料	Copper alloy
☞ 导电体表面镀层	Sn,Plated
☞ 颜色	绿/黑/蓝/灰/橙/红

技术数据

☞ 额定电流（IEC）	76A
☞ 额定电压（IEC）	1000V
☞ 过压类别	III/III/ II
☞ 污染等级	3 2 2
☞ 额定冲击电压	8.0KV 8.0KV 8.0KV
☞ 额定电流（UL）	70A 70A 5A
☞ 额定电压(UL)	600V 600V 600V
☞ 硬导线截面积	0.75-16.0mm ²
☞ 柔性导线截面积	0.75-16.0mm ²
☞ 柔性导线截面积，带绝缘管套	0.75-16.0mm ²
☞ 锁线螺钉规格	-
☞ 锁线螺钉扭矩	-
☞ 固定螺钉规格	-
☞ 剥线长度	18-20mm

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

邮编：315303

Switchboard: +86 574-63288158

总机：+86 574-63288158

Fax: +86 574-63288170

传真：+86 574-63288170

E-mail：supucontact@supu.cn

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

服务热线：400-626-6336



官方微信