



产品描述: 间距: 5.08mm 额定电压: 250V
额定电流: 10A 颜色: 可定制

Figure 1: PCB layout of the 12-channel 100-Gbit/s optical receiver. The figure includes three views: a top view, a side view, and a detailed PCB layout. The top view shows a rectangular package with dimensions 25.4 mm by 23.70 mm. It features 12 channels, each with a laser and a photodiode. The side view shows a height of 12.0 mm and a base width of 22.10 mm. The detailed PCB layout shows the internal structure with dimensions 7.62 mm, 5.08 mm, 2.54 mm, 10.16 mm, and 5.08 mm. It also includes a reference hole diameter of 1.70 mm and a formula $5.08 \times (P/2 - 1)$.

参数

产品型号	MC-DPAB5.08H26-F-0001
产品间距	5.08
接线位数	26
接线方式	-

☞ 防护等级	IP20
☞ 工作温度	-40~+105°C
☞ 绝缘材料	PA66
☞ 绝缘材料组别	I
☞ 导电体材料	Copper alloy
☞ 导电体表面镀层	Sn,Plated
☞ 颜色	绿/黑/蓝/灰/橙/红

技术数据

☞ 额定电流（IEC）	10A
☞ 额定电压（IEC）	250V
☞ 过压类别	III
☞ 污染等级	3
☞ 额定冲击电压	4.0KV
☞ 额定电流（UL）	15A - 15A
☞ 额定电压(UL)	300V - 311V
☞ 硬导线截面积	-
☞ 柔性导线截面积	-
☞ 柔性导线截面积，带绝缘管套	-
☞ 锁线螺钉规格	-
☞ 锁线螺钉扭矩	-
☞ 固定螺钉规格	-
☞ 固定螺钉扭矩	-
☞ 剥线长度	-

⌘ 使用组别	B/C/D
⌘ 额定接线容量	-

商业数据

⌘ 订货号	MC-DPAB5.08H26-F-0001
-------	-----------------------

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303	邮编：315303
Switchboard: +86 574-63288158	总机：+86 574-63288158
Fax: +86 574-63288170	传真：+86 574-63288170
E-mail：supucontact@supu.cn	E-mail：supucontact@supu.cn
Service Hotline: 400-626-6336	服务热线：400-626-6336



官方微信