



产品描述: 间距: 5.08mm 额定电压: 250V
额定电流: 10A 颜色: 可定制

Figure 1: PCB layout of the 12-channel 100-pin connector. The figure includes three views: a top view, a side view, and a detailed PCB layout. The top view shows a 12-pin connector with dimensions 2.54, 10.16, 5.08, and $5.08 \times (P/2 - 1)$. The side view shows a 12-pin connector with dimensions 12.0, 23.70, 10.16, and 2.0. The detailed PCB layout shows a 12-pin connector with dimensions 7.62, 5.08, 2.54, 10.16, and $5.08 \times (P/2 - 1)$. The layout also includes a reference hole diameter of 1.70 and a label "PCB LAYOUT".

参数

☞ 产品型号	MC-DPAB5.08H44-F-0001
☞ 产品间距	5.08
☞ 接线位数	44
☞ 接线方式	-

⌘ 防护等级	IP20
⌘ 工作温度	-40~+105°C
⌘ 绝缘材料	PA66
⌘ 绝缘材料组别	I
⌘ 导电体材料	Copper alloy
⌘ 导电体表面镀层	Sn,Plated
⌘ 颜色	绿/黑/蓝/灰/橙/红

技术数据

⌘ 额定电流（IEC）	10A
⌘ 额定电压（IEC）	250V
⌘ 过压类别	III
⌘ 污染等级	3
⌘ 额定冲击电压	4.0KV
⌘ 额定电流（UL）	15A - 15A
⌘ 额定电压(UL)	300V - 320V
⌘ 硬导线截面积	-
⌘ 柔性导线截面积	-
⌘ 柔性导线截面积，带绝缘管套	-
⌘ 锁线螺钉规格	-
⌘ 锁线螺钉扭矩	-
⌘ 固定螺钉规格	-
⌘ 固定螺钉扭矩	-
⌘ 剥线长度	-

⌘ 使用组别	B/C/D
⌘ 额定接线容量	-

商业数据

⌘ 订货号	MC-DPAB5.08H44-F-0001
-------	-----------------------

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303	邮编：315303
Switchboard: +86 574-63288158	总机：+86 574-63288158
Fax: +86 574-63288170	传真：+86 574-63288170
E-mail：supucontact@supu.cn	E-mail：supucontact@supu.cn
Service Hotline: 400-626-6336	服务热线：400-626-6336



官方微信