

产品名称:MC-TC-B10.0H10P-0001

颜色：可定制



Figure 1: PCB layout of the module. The figure includes four views: a top view, a side view, a front view, and a rear view. The top view shows a square module with dimensions 29.00 x 30.00. It features a central circular area with "SUPU" and "NC-TC19.2H" markings. The side view shows a height of 15.00. The front view shows a width of 10.00 x (P-1) and a height of 11.50. The rear view shows a width of 10.00 x P + 1.80 and a height of 11.50. Various mounting holes and dimensions are specified throughout the layout.

参数

☞ 产品型号	MC-TC-B10.0H10P-0001
☞ 产品间距	10
☞ 产品层数	单层
☞ 接线位数	10

☞ 接线方式	直插弹簧接线
☞ 防护等级	IP20
☞ 工作温度	-40~+105℃
☞ 绝缘材料	PA66
☞ 绝缘材料组别	I
☞ 导电体材料	Copper alloy
☞ 导电体表面镀层	Sn,Plated
☞ 颜色	绿/黑/蓝/灰/橙/红

技术数据

☞ 额定电流（IEC）	76A
☞ 额定电压（IEC）	1000V
☞ 过压类别	III/III/ II
☞ 污染等级	3 2 2
☞ 额定冲击电压	8.0KV 8.0KV 8.0KV
☞ 额定电流（UL）	70A 70A 5A
☞ 额定电压(UL)	600V 600V 600V
☞ 硬导线截面积	0.75-16.0mm ²
☞ 柔性导线截面积	0.75-16.0mm ²
☞ 柔性导线截面积，带绝缘管套	0.75-16.0mm ²
☞ 锁线螺钉规格	-
☞ 锁线螺钉扭矩	-
☞ 固定螺钉规格	-
☞ 固定螺钉扭矩	-

剥线长度	18-20mm
使用组别	B/C/D
额定接线容量	20-4AWG

商业数据

订货号	MC-TC-B10.0H10P-0001
-----	----------------------

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303	邮编：315303
Switchboard: +86 574-63288158	总机：+86 574-63288158
Fax: +86 574-63288170	传真：+86 574-63288170
E-mail：supucontact@supu.cn	E-mail：supucontact@supu.cn
Service Hotline: 400-626-6336	服务热线：400-626-6336



官方微信