

产品描述: 间距：5.0mm 额定电压：320V
额定电流：17.5A 连接方式：直插弹簧接线
颜色：可定制



Technical drawings of the MC-T15.0 component, showing dimensions and layout details:

- Top View:** Shows the component's footprint with dimensions: 8.50 (F) for the width of the central area and 5.00 for the pitch between mounting holes. The total width is 5.00x(P-1) + 2.10.
- Side View (Left):** Shows the component's profile with dimensions: 13.50 Ref. (F) for the total height, 12.30 (F) for the height of the main body, and 5.50 ± 0.15 for the mounting pad width. The component is labeled "SUPU MC-T15.0".
- Side View (Right):** Shows the component's profile with dimensions: 3.50 ± 0.20 (F) for the height of the main body and 0.40 for the mounting pad width.
- PCB LAYOUT:** Shows the component's footprint with dimensions: 5.00 for the pitch between mounting holes, 5.50 for the height of the mounting pads, and 1.60 for the width of the mounting pads. The total width is 5.00x(P-1) + 4.20 (F). The component is labeled "PCB LAYOUT".
- Bottom View:** Shows the component's footprint with dimensions: 5.00 for the pitch between mounting holes, 0.80 for the width of the mounting pads, and 2.10 for the total width. The component is labeled "Dim. a = 5.00x(P-1)".

4

☞ 接线方式	直插弹簧接线
☞ 防护等级	IP20
☞ 工作温度	-40~+130℃
☞ 绝缘材料	PA66
☞ 绝缘材料组别	I
☞ 导电体材料	Copper alloy
☞ 导电体表面镀层	Sn,Plated
☞ 颜色	绿/黑/蓝/灰/橙/红

技术数据

☞ 额定电流（IEC）	17.5A
☞ 额定电压（IEC）	200V
☞ 过压类别	III/III/ II
☞ 污染等级	3 2 2
☞ 额定冲击电压	2.5KV 2.5KV 2.5KV
☞ 硬导线截面积	0.2-1.5mm ²
☞ 柔性导线截面积	0.2-1.5mm ²
☞ 柔性导线截面积，带绝缘管套	0.2-1.5mm ²
☞ 锁线螺钉规格	-
☞ 锁线螺钉扭矩	-
☞ 固定螺钉规格	-
☞ 剥线长度	8-9mm

商业数据

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

邮编：315303

Switchboard: +86 574-63288158

总机：+86 574-63288158

Fax: +86 574-63288170

传真：+86 574-63288170

E-mail：supucontact@supu.cn

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

服务热线：400-626-6336



官方微信