



产品描述: 间距: 5.0mm 额定电压: 320V

额定电流：10A 颜色：可定制

Technical drawing of the 10-pin connector showing front, side, and top views with dimensions:

- Front View (Left):** Shows a width of 3.50 ± 0.30 and a height of 1.00 ± 0.05 .
- Side View (Middle):** Shows a total height of 28.45 and a pin height of 20.00. The pin pitch is 2.50.
- Top View (Right):** Shows a pin pitch of 2.50 and a total width of 22.00. The pin diameter is $\phi 1.40$ (建议孔径尺寸). The overall dimensions are labeled as Dim.a and Dim.b.

产品型号

MC-DPA5.0V22-F-0002

产品间距

5

产品层数

多层

接线位数

22

☞ 接线方式	-
☞ 防护等级	IP20
☞ 工作温度	-40~+105℃
☞ 绝缘材料	PA66
☞ 绝缘材料组别	I
☞ 导电体材料	Copper alloy
☞ 导电体表面镀层	Sn,Plated
☞ 颜色	绿/黑/蓝/灰/橙/红

技术数据

☞ 额定电流（IEC）	10A
☞ 额定电压（IEC）	320V
☞ 过压类别	III III II
☞ 污染等级	3 2 2
☞ 额定冲击电压	4.0KV 4.0KV 4.0KV
☞ 硬导线截面积	-
☞ 柔性导线截面积	-
☞ 柔性导线截面积，带绝缘管套	-
☞ 锁线螺钉规格	-
☞ 锁线螺钉扭矩	-
☞ 固定螺钉规格	-
☞ 固定螺钉扭矩	-
☞ 剥线长度	-
☞ 使用组别	B/C/D

商业数据

 订货号

MC-DPA5.0V22-F-0002

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail：supucontact@supu.cn

Service Hotline: 400-626-6336

邮编：315303

总机：+86 574-63288158

传真：+86 574-63288170

E-mail：supucontact@supu.cn

服务热线：400-626-6336



官方微信