



产品描述: 间距: 3.81mm 额定电压: 160V
额定电流: 8A 颜色: 可定制

Figure 1: Dimensions of the PCB layout. The figure shows a side view and a top view of a PCB layout. The side view shows a total height of 14.50, with a base of 6.60 and a top section of 1.10. The top view shows a rectangular layout with dimensions $3.81 \times P + 10.39$ and $3.81 \times P + 5.19$. It includes a grid of holes with a pitch of 3.81 and a diameter of 1.50. Other dimensions include 4.50, 3.40, 0.60, 7.10, 6.85, and 1.20.

产品型号

MC-RU3.81SV20-F-0001

产品间距

3.81

产品层数

单层

接线位数

20

☞ 接线方式	-
☞ 防护等级	IP20
☞ 工作温度	-40~+105℃
☞ 绝缘材料	PA66
☞ 绝缘材料组别	I
☞ 导电体材料	Copper alloy
☞ 导电体表面镀层	Sn,Plated
☞ 颜色	绿/黑/蓝/灰/橙/红

技术数据

☞ 额定电流（IEC）	8A
☞ 额定电压（IEC）	160V
☞ 过压类别	III/III/ II
☞ 污染等级	3 2 2
☞ 额定冲击电压	2.5KV2.5KV2.5KV
☞ 额定电流（UL）	8A - 8A
☞ 额定电压(UL)	300V - 300V
☞ 硬导线截面积	-
☞ 柔性导线截面积	-
☞ 柔性导线截面积，带绝缘管套	-
☞ 锁线螺钉规格	-
☞ 锁线螺钉扭矩	-
☞ 固定螺钉规格	M2.5
☞ 固定螺钉扭矩	0.3N.M

剥线长度	-
使用组别	B/C/D
额定接线容量	-

商业数据

订货号	MC-RU3.81SV20-F-0001
-----	----------------------

宁波速普电子有限公司

Address: No. 150, Xinxing 4th Road, 地址：浙江省慈溪市高新技术产业开发区新兴四路150号
High-tech Industrial Development
Zone, Cixi City, Zhejiang Province,
China

Zip code: 315303	邮编：315303
Switchboard: +86 574-63288158	总机：+86 574-63288158
Fax: +86 574-63288170	传真：+86 574-63288170
E-mail：supucontact@supu.cn	E-mail：supucontact@supu.cn
Service Hotline: 400-626-6336	服务热线：400-626-6336



官方微信